

HAND
HAND ENGINEERING LTD

email: info@handengineering.com

Tel: + 353 44 9666504

www.handengineering.com



Lavender Harvester Range

LH45



Standard Specification

- Four floor chains hydraulically driven.
- Two hydraulic cylinders lifting elevator.
- 300mm ground clearance.
- Adjustable mowing height.
- Pivoting bogey axle.
- Galvanised floor and side sheeting.
- Safety latch on mower and drawbar for road transport.
- In cab electronic controls.
- Telescopic drawbar support.
- Double wide angle PTO shaft.
- L.E.D. rear lights.
- Shotblasted.
- Two pack primer and paint.

Optional Extras

- Rear view camera to aid filling, unloading and reversing.



1.65 Drum Mower



Telescopic Drawbar Support



Adjustable Track Width



Floating Adjustable Head



Hydraulic Cylinder Lifting Elevator



Adjustable Cutting Height

Tel: + 00 353 44 9666 504

www.handengineering.com

email: info@handengineering.com

Hand Engineering Limited, Dromone, Oldcastle, Co. Meath, Ireland A82 K2P6



Model	Capacity m3	Mower Type	Mower Width (mm)	Elevator Width (mm)	Track Width (mm)	Chassis Width (mm)	Body Width (mm) * Height	Body Length (mm)	Overall Height (mm)	Wheel Width
LH45	15	Drum	1600	1250	1620/1680	1640	1640 * 2400	3900	3500	12.5/80/18
LH75	21	Drum	1600	1250	1620/1680	1640	1640 * 2400	5300	3500	12.5/80/18